

State Price Quote Specification
**TYPE D60—BID AS 48 PASSENGER
 DIESEL**

Vendor: BRYSON

Use this document to bid both non-lift and lift buses for 35–60 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS	VENDOR SPECIFICALLY IDENTIFY ITEM BID	
	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	Price of items bid will establish the state cost.	
Seating Capacity	48 passenger based upon an average center-to-center seat spacing of at least 27.5".	Capacity w/o lift <u>48</u>	
		Capacity w/lift <u>37</u>	
Alternator	240 amp minimum. Lift-equipped or air-conditioned. Manufacturer recommended capacity.	Mfr. <u>LEECE NEVILLE</u>	
		Amps output w/o lift or A.C. <u>240</u>	
		Amps output w/lift or A.C. <u>240</u>	
Auxiliary Fans	2 fans, 6" maximum, mounted to right and left windshield and service door.	Mfr. <u>GSS USA</u>	
Axle—Front	10,000 lb. minimum.	Mfr. <u>HENDRICKSON</u>	
		Capacity <u>12,000</u>	
Axle—Rear	19,000 lb. minimum.	Mfr. <u>DANA</u>	
		Capacity <u>21,000</u>	
Axle Oil Seals	Front and rear oil bath, or maintenance free sealed greased bearings.	Mfr. <u>SKF</u>	
Axle Ratio	Must comply with power and gradeability formula. Refer to Washington State School Bus Specifications Manual.	Ratio <u>5.29</u>	
Back-up Lights	All required backup lights to be LED (Light Emitting Diode). Refer to Washington State School Bus Specification's Manual.	Round: <input checked="" type="checkbox"/> Diameter <u>4"</u> Other: <input type="checkbox"/> Square inches _____	
Battery(ies)	1200 CCA 12 volt minimum to be mounted in body battery compartment w/o lift.	Size/group w/o lift <u>31</u> CCA <u>2100</u>	
	1400 CCA 12 volt minimum to be mounted in body battery compartment w/lift.	Size/group w/lift <u>31</u> CCA <u>2100</u>	
Battery Compartment	Battery storage tray must be large enough to accommodate batteries as specified in chassis section.	<input checked="" type="checkbox"/> Swing out <input type="checkbox"/> Roll out	
Brakes	Hydraulic disc. Refer to Washington State School Bus Specifications Manual.	Size Front <u>70 MM</u> Rear <u>70 MM</u>	

State Price Quote Specification
**TYPE D60—BID AS 48 PASSENGER
 DIESEL**

Use this document to bid both non-lift and lift buses for 35–60 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.	
Door, Service	Power operated.	<input type="checkbox"/> Air <input checked="" type="checkbox"/> Electric <input type="checkbox"/> Other	<input type="checkbox"/> Folding <input checked="" type="checkbox"/> Split, Outward opening <input type="checkbox"/> Other
Engine	Diesel—180 H.P. minimum.	Engine mfr. <u>CUMMINS</u> Model or liters <u>B6.7L</u> Net torque <u>600</u> @ <u>1600</u> R.P.M Net H.P. <u>200</u> @ <u>2400</u> R.P.M Location: Rear <input type="checkbox"/> Forward <input checked="" type="checkbox"/>	
Engine Heater	Engine manufacturers recommended in-block heater.	Watts <u>750</u> Volts <u>120</u> Mfr. <u>PHILLIPS</u>	
Engine Temperature	To be controlled electronically, by fan clutch/drive, or shutters.	Mfr. <u>HORTON</u> <input type="checkbox"/> Electronic <input checked="" type="checkbox"/> Fan clutch <input type="checkbox"/> Shutters	
Fuel Tank	60 gallon minimum.	Capacity <u>60 GALLONS</u>	
Heaters	Minimum of 3 heaters; 1 front, 1 center, 1 rear. Shutoff valves at engine for all heaters. Two-speed motors. Must include recirculating pump.	Front B.T.U. <u>90,000</u> Center B.T.U. <u>50,000</u> Rear B.T.U. <u>50,000</u> , Total B.T.U. <u>190,000</u>	
Lights	LED (Light Emitting Diode). Includes Clearance Lights, Stop Lights—7", Taillights, Turn Signals, Eight-Light System, and Dome-Light System.	Check if as specified <input checked="" type="checkbox"/> If not, explain. _____	
P.A. System	AM/FM/PA radio with 2 interior and 1 exterior speakers.	Mfr. <u>MUSIC WAVE</u> Model No. <u>MFG STD</u>	
Seat Spacing	To permit specified passenger capacity based on an average center-to-center seat spacing of at least 27.5".	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: w/o lift <u>278"</u> w/lift <u>278"</u> Mfg.'s C/C seat measurement of vehicle (inches): w/o lift <u>27.5"</u> w/lift <u>27.5"</u>	

State Price Quote Specification
**TYPE D60—BID AS 48 PASSENGER
 DIESEL**

Use this document to bid both non-lift and lift buses for 35–60 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.
Steering Wheel	Tilt and telescoping column.	Check if as specified <input checked="" type="checkbox"/>
Step Tread	Studded or pebbled top tread covering.	Mfr. <u>PROFUSION INDUSTRIES</u>
Tires	6 first quality, radial ply. No low profile tires.	Mfr. <u>ONE OF FIVE MAJOR BRANDS</u> Size <u>11R 22.5</u> Load range <u>H</u>
Toolbox	Exterior, manufacturer standard.	Size (cubic feet) <u>3.16</u>
Transmission	Automatic—Allison, PTS 2500 or equal.	Mfr. <u>ALLISON</u> Model no. <u>2500 PTS</u> Net input torque <u>600</u> Net input H.P. <u>300</u>
Two-way Communications	45-watt, VHF, mil. spec.	Mfr. <u>KENWOOD</u> Model No. <u>NX3720HVK</u>
Wheels	6 to be compatible with tire size.	Size <u>22.5</u> Rim width <u>8.25</u>

State Price Quote Specification
**TYPE D60—BID AS 48 PASSENGER
 DIESEL**

Vendor: BRYSON

Use this document to bid both non-lift and lift buses for 35–60 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.
SPECIAL NEEDS REQUIREMENTS—CHASSIS AND BODY		
Wheelchair Lift—Installed	Must meet state specification. Platform shall be a minimum of 32" x 52".	Mfr. <u>BRAUN</u> Model No. <u>NCL-919-FIB2</u>
Wheelchair/ Occupant Tie-down System—Installed	Must meet state specification.	Mfr. <u>Q-STRAINT</u> Model No. <u>Q-8106-L2</u>
ADDITIONAL REQUIREMENTS—CHASSIS AND BODY		
Line Setting Ticket	Legible copy of manufacturer's Line Setting Ticket will be delivered with each vendor's packet at the time of delivery of the bus.	Check if as specified <input checked="" type="checkbox"/>
Owner's/Operator's Handbook	One copy of the chassis manufacturer's owner's/operator's handbook or manual will be furnished with each bus at time of delivery.	Check if as specified <input checked="" type="checkbox"/>
Repair Manuals	A complete set of chassis, engine, transmission, and body repair manuals, including wiring diagram for all components, will be made available at time of delivery, with instructions available on accessing repair materials.	Check if as specified <input checked="" type="checkbox"/>
Service and Cleaning	Cleaning and service by vendor prior to delivery will include: <ul style="list-style-type: none"> • Chassis lubrication. • Check fluid levels: verify all are at recommended full levels. • Cooling system protected at -20°F. • Interior and exterior will be clean (including glass). • All systems (electric, air, hydraulic, mechanical, and manual) be inspected to ensure proper operation at time of delivery. • All components and accessories will be installed and operational at time of delivery. 	Check if as specified <input checked="" type="checkbox"/>
Warranty	A complete copy of all warranty agreements will be furnished at time of delivery.	Check if as specified <input checked="" type="checkbox"/>



Washington Office of Superintendent of
PUBLIC INSTRUCTION
2024-2025

STUDENT TRANSPORTATION
Old Capitol Building
PO BOX 47200
Olympia, WA 98504-7200
(360) 725-6120 TTY (360) 664-3631

VEHICLE DATA SHEET AND OFFICIAL PRICE QUOTATION
TYPE D60—BID AS 48 PASSENGER (DIESEL)

VENDOR'S COMPANY NAME BRYSON SALES & SERVICE OF WASHINGTON, INC.	REPRESENTATIVE'S NAME BRANDON BRYSON	TELEPHONE NUMBER 425-953-2820
ADDRESS 2407 GIBSON RD. EVERETT, WA 98204	Estimated delivery date to school district from time purchase order is received: <u>150-180</u> Firm where engine and chassis can be serviced or repaired, and parts obtained: <u>BRYSON</u> Firm where body can be serviced or repaired, and parts obtained: <u>BRYSON</u>	

BODY

MAKE BLUE BIRD	Warranty: Years <u>1</u> Miles <u>12,000</u>	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: w/o lift <u>278"</u> w/lift <u>278"</u>	Equipped seating capacity: w/o lift <u>48</u> w/lift <u>37</u>
MODEL T3FE 2903	YEAR 2025	Seat color: <u>BROWN</u> Floor color: <u>BLACK</u>	Overall vehicle length (inches): w/o lift <u>352.92</u> w/lift <u>352.92</u>

CHASSIS

MAKE BLUE BIRD	Warranty: Years <u>1</u> Miles <u>12,000</u>	MANUFACTURER CUMMINS	Torque: <u>600</u> @ <u>1600</u> RPM H.P.: <u>200</u> @ <u>2400</u> RPM
MODEL T3FE 2903	YEAR 2025	Wheelbase: <u>141"</u>	MODEL B6.7L
			YEAR 2025
			C.I.D. or Liters: <u>6.7L</u> Fuel type: <u>DIESEL</u>

ENGINE

TRANSMISSION

MANUFACTURER ALLISON	Warranty: Years <u>5</u> Miles <u>100,000</u>	Battery type/grp: <u>31</u> <u>31</u>
MODEL 2500 PTS	Speeds forward: <u>5</u>	Number batteries: <u>3</u> <u>3</u>
	Warranty: Years <u>7</u> Miles <u>UNLIM</u>	Total CCA: <u>2100</u> <u>2100</u>
	Number of cylinders: <u>6</u> Inline <u>X</u> V-type <u>_____</u>	

QUOTED PRICE

Quoted price is based upon payment within 30 days after delivery to the school district (without sales tax).

Bid—w/o lift \$ 189,888.00

Bid—w/lift \$ 196,120.00

VENDOR REPRESENTATIVE'S SIGNATURE
Brandon Bryson

DATE
08/02/2024

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

Vendor: BRYSON

C60 C77 D60 D84

Use this document to bid both non-lift and lift buses.

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Activity Securement Seating	2-passenger position seats with lap-shoulder belts in all passenger positions.	Passenger Capacity <u>30</u> Cost \$ <u>12,217.00</u>	
Air Conditioning	To cool passenger compartment as required in the Washington State School Bus Specifications manual.	Mfr. <u>MCC AC-12IW1IW1133D</u> Cost \$ <u>15,657.00</u>	
Alternate Fuel <input type="checkbox"/> Electric	Must comply with power and gradeability formula. Refer to Washington State School Bus Specifications manual. Must comply with all of the requirements of FMVSS No. 305.	Mfr. <u>N/A</u> <input type="checkbox"/> Cost \$ <u>N/A</u> <input type="checkbox"/> Electric Cost \$ <u>N/A</u>	
Alternator	Available options.	Cost \$ <u>INCLUDED</u>	Capacity <u>240 AMP</u>
		Cost \$ <u>506.00</u>	Capacity <u>280 AMP</u>
		Cost \$ <u>721.00</u>	Capacity <u>325 AMP</u>
Anti-spray Device	Rubber fender extenders.	Type C: Cost \$ <u>215.00</u> Type D: Cost \$ <u>414.00</u>	
Back-up Alarm	Must meet state specification.	Mfr. <u>ECCO VARIABLE DBA</u> Cost \$ <u>230.00</u>	
Brakes	4-wheel hydraulic disk brake.	Cost \$ <u>INCLUDED</u>	Deduct \$ <u>0.00</u>
Brakes	Air, Drum or Disc. Refer to Washington State School Bus Specifications manual.	Disc Cost \$ <u>3,888.00</u> Drum Cost \$ <u>INCLUDED</u>	Disc Deduct \$ <u>N/A</u> Drum Deduct \$ <u>N/A</u>
Color	Exterior white roof.	Cost \$ <u>INCLUDED</u>	
Door Locks	Vandal lock system on all exterior doors.	Cost \$ <u>559.00</u>	
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Non-Air	Air
		Mfr. <u>NATIONAL</u>	Mfr. <u>NATIONAL</u>
		Cost \$ <u>INCLUDED</u>	Cost \$ <u>330.00</u>
Fire Suppression System	Jomarr VT-6-E-NAF, or equal engine compartment fire suppression system of appropriate size to be installed according to manufacturer recommendation.	Mfr. <u>AMEREX VH25 ABC FOUR NOZZLE</u> Cost \$ <u>5,967.00</u>	
Floor Color	Nonstandard color.	Cost \$ <u>459.00</u>	

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

Vendor: BRYSON

C60 C77 D60 D84

Use this document to bid both non-lift and lift buses.

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Fuel Tank	Larger fuel capacity (Diesel only).	Size: <u>N/A</u>	Cost \$ <u>N/A</u>
Fuel Tank	Larger fuel capacity (Propane only).	Size: <u>N/A</u>	Cost \$ <u>N/A</u>
Headlights	Halogen.	Cost \$ <u>0.00</u>	
Headlights	L.E.D.	Cost \$ <u>INCLUDED</u>	
Heater (Auxiliary water)	Auxiliary fuel-fired heating systems. Refer to Washington State School Bus Specifications Manual, page 27.	Brand: <u>WEBASTO</u>	Model: <u>17,000 BTU</u>
		Cost \$ <u>2,067.00</u>	
Noise Reduction	Exceeding minimum specifications.	Driver compartment	Cost \$ <u>INCLUDED</u>
		Engine compartment	Cost \$ <u>INCLUDED</u>
		Full acoustical headliner	Cost \$ <u>936.00</u>
Retarder	Manufacturer's standard.	Driveline <input checked="" type="checkbox"/>	Cost \$ <u>17,500.00</u>
		Exhaust <input checked="" type="checkbox"/>	Cost \$ <u>110.00</u>
		Transmission <input type="checkbox"/>	Cost \$ <u>N/A</u>
Seat Belt Ready Seat	3-passenger position seat with belts.	Cost \$ <u>385.00 PER SEAT</u>	
Seating System	Identical, non-lift bus with lap-shoulder seat belt system installed in all positions.	2 by 2 Cost \$ <u>6,770.00</u>	
		Capacity <u>30</u>	
		3 by 2 Cost \$ <u>7,929.00</u>	
		Capacity <u>40</u>	
		3 by 3 Cost \$ <u>8,465.00</u>	
		Capacity <u>48</u>	

Vendor: BRYSON

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

C60 C77 D60 D84

Use this document to bid both non-lift and lift buses.

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Storage Compartments	Largest available for unit bid.	Left side <u>N/A</u> cubic feet. Cost \$ <u>N/A</u>	Right-side <u>16</u> cubic feet. Cost \$ <u>1,074.00</u>
		Push-thru <u>N/A</u> cubic feet. Cost \$ <u>N/A</u>	
Strobe Light	Exterior roof mounted white strobe light.	Mfr. <u>ECCO</u> Model No. <u>7460 LED CLEAR LENS</u> Cost \$ <u>223.00</u>	
Student Protection System—Installed	Electronic system to insure driver post-trip inspection of passenger compartment.	Mfr. <u>BLUE BIRD</u> Model No. <u>DA01</u> Cost \$ <u>199.00</u>	
Suspension	Air ride (Air brake system only).	Front	Rear
		Cost \$ <u>1,450.00</u>	Cost \$ <u>1,649.00</u>
Toolbox	Interior, manufacturer standard.	Cost \$ <u>84.00</u>	Deduct \$ <u>N/A</u>
Traction Device	Automatic chains.	Mfr. <u>ON SPOT</u> Cost \$ <u>4,899.00</u>	
Traction Device	Sanders.	Capacity <u>100 LBS.</u> Cost \$ <u>2,909.00</u>	
Transmission	Automatic—Allison, PTS 3000 or equal.	Mfr. <u>ALLISON</u> Model No. <u>3000 PTS</u> Cost \$ <u>6,573.00</u>	
Vehicle Securement System	Must meet state specification.	Mfr. <u>BLUE BIRD</u>	Cost \$ <u>794.00</u>

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

C60 C77 D60 D84

Use this document to bid both non-lift and lift buses.

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Video Camera Systems—Installed	Digital audio/video system for monitoring the passenger compartment with more than two cameras.	Mfr. <u>REI</u> Model No. <u>HD6-600W-4-500GB HDD</u> Cost \$ <u>2,493.00</u> How many cameras <u>4</u>	
Video Camera Systems—Stop Sign Camera—Installed	Must meet state specification.	Stand Alone System	Added to Interior System
		Mfr. <u>REI</u> Model No. <u>HD6-600W</u> Cost \$ <u>2,033.00</u> How many cameras <u>2</u>	Mfr. <u>REI</u> Model No. <u>MB AHD WRR</u> Cost \$ <u>277</u> How many cameras <u>1</u>
Warning Light Monitor	16 light monitoring system.	Incandescent	LED Lights
		Cost \$ <u>284.00</u>	Cost \$ <u>284.300</u>
Additional Wheelchair/Occupant Tie-down System—Installed	Must meet state specification.	Mfr. <u>Q-STRAINT</u> Model No. <u>Q-8106-L2</u> Cost per station \$ <u>598.00</u>	
Windows	Laminated passenger-compartment side or rear glass.	Side Cost \$ <u>3,514.00</u> Rear Cost \$ <u>1,490.00</u> Both Cost \$ <u>5,004.00</u>	
Windows	Tinted.	Cost \$ <u>INCLUDED</u>	
Windows	Thermal pane, left of driver and service door.	Cost \$ <u>601.00</u>	