

# State Price Quote Specification TYPE D—84 PASSENGER, REAR ENGINE Use this document to bid both non-lift and lift buses for 61 – 84 capacity

PART I Vendor: <u>SCHETKY NW SALES</u>

THOMAS BUILT BUS

ITEM	SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.		
Seating Capacity	84 passenger maximum design capacity seated for 78 passenger.	Capacity w/o lift <u>78</u> Capacity w/lift <u>N/A</u>		
Alternator	240 amp minimum. Lift-equipped or air-conditioned. Manufacturer recommended capacity.	Mfr. <u>LEECE-NEVILLE</u> Amps output w/o lift or A.C. <u>240</u> Amps output w/lift or A.C. N/A		
Auxiliary Fans	2 fans, 6" maximum, mounted to right and left windshield and service door.	Mfr. <u>BERGSTROM</u>		
Axle—Front	13,200 lb. minimum total suspension GVWR.	Mfr. <u>DETROIT</u> Capacity <u>13,200-LB</u>		
Axle—Rear	23,000 lb. minimum total suspension GVWR.	Mfr. <u>DETROIT 23,000-LB</u> Capacity		
Axle Oil Seals	Front and rear oil bath, or maintenance free sealed greased bearings.	Mfr. <u>CR</u>		
Axle Ratio	Must comply with power and gradeability formula. Refer to Washington State School Bus Specifications Manual.	Ratio <u>5.57</u>		
Back-up Lights	All required backup lights to be LED (Light Emitting Diode). Refer to Washington State School Bus Specification's Manual.	Round:   Diameter     Other:   Image: Square inches and the square inches and th		
Battery(ies)	1400 CCA 12 volt to be mounted in body battery compartment.	Number of batteries     2       CCA 1900		
Battery Compartment	Battery storage tray must be large enough to accommodate batteries as specified in chassis section.	□ Swing out		
Brakes	Air: Drum or Disc. If Drum, minimum 16.5" x 6" front, minimum 16.5" x 8" rear. Refer to Washington State School Bus Specifications Manual.	Disc         Front         □         Rear         □           Drum         Front         ⊠         Rear         ⊠           Size <u>16.5X6</u> Rear <u>16.5X8 5/8</u>		
Door, Service	Power operated.	<ul> <li>□ Folding</li> <li>□ Other</li> <li>□ Roll out</li> <li>☑ Split, Outward opening</li> </ul>		
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Mfr. <u>NATIONAL</u>		

## State Price Quote Specification TYPE D—84 PASSENGER, REAR ENGINE Use this document to bid both non-lift and lift buses for 61 – 84 capacity

PART I (cont.) Vendor: <u>SCHETKY NW SALES</u> THOMAS BUILT BUS

ITEM	SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.		
Engine	Diesel—280 H.P. minimum, located in the rear.	Engine mfr. <u>CUMMII</u> Model or liters <u>B6.7L</u> Net torque <u>660</u> Net H.P. 280		R.P.M R.P.M
Engine Heater	Engine manufacturers recommended in-block heater.	Watts 750         Volts 12           Mfr. PHILLIPS		
Engine Temperature	To be controlled electronically, by fan clutch/drive, or shutters.	Mfr. <u>EATON</u> ⊠ Fan clutch	_ □ Electron □ Shutter	
Fuel Tank	100 gallon minimum.	Capacity 100 GALLON		
Heaters	Minimum of 3 heaters; 1 front, 1 center, 1 rear. Shutoff valves at engine for all heaters. Two-speed motors. Must include recirculating pump.	Front B.T.U. <u>90.000</u> Center B.T.U. <u>50,000</u> Rear B.T.U. <u>50,000</u> Total B.T.U. <u>190,000</u>		
Lights	LED (Light Emitting Diode). Includes Clearance Lights, Stop Lights–7", Taillights, Turn Signals, Eight-Light System, and Dome-Light System.	Check if as specified ⊠ If not, explain.		
P.A. System	AM/FM/PA radio with 4 interior and 1 exterior speakers.	Mfr. <u>DELPHI</u> Model No. <u>DEA700</u>		
Seat Spacing	78 passenger based upon manufacturer's maximum seat spacing.	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: <u>396.5</u> inches Mfg.'s C/C seat measurement: <u>30</u> inches		
Steering Wheel	Tilt and telescoping column.	Check if as specified		
Step Tread	Studded or pebbled top tread covering.	Mfr. KOROSEAL		
Tires	6 first quality, radial ply. No low profile tires.	Mfr. <u>HANKOOK</u> Size <u>11R22.5</u> Load range <u>H</u>		

### State Price Quote Specification TYPE D—84 PASSENGER, REAR ENGINE

PART I (cont.) Vendor: <u>SCHETKY NW SALES</u> <u>THOMAS BUILT BUS</u>

#### Use this document to bid both non-lift and lift buses for 61 - 84 capacity

ITEM	SPECIFICATIONS	VENDOR SPECIFICALLY IDENTIFY ITEM BID
	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	Price of items bid will establish the district cost.
Toolbox	Exterior, manufacturer standard.	Size (cubic feet) 6.9
Transmission	Automatic—Allison, PTS 3000 or equal.	Mfr. ALLISON
		Model no. 3000PTS
		Net input torque 660
		Net input H.P. 280
Two-way	45-watt, VHF, mil. spec.	Mfr. MOTOROLA
Communications		Model No. CM300D
Wheels	6 to be compatible with tire size.	Size <u>22.5"</u>
		Rim width 8.25"
	SPECIAL NEEDS REQUIREMENTS—CHASSIS AND BODY	
Wheelchair Lift—	Must meet state specification. Platform shall be a minimum of 32" x	Mfr. <u>N/A</u>
Installed	52".	Model No
Wheelchair/	Must meet state specification.	Mfr
Occupant Tie- down System— Installed		Model No

## State Price Quote Specification TYPE D—84 PASSENGER, REAR ENGINE Use this document to bid both non-lift and lift buses for 61 – 84 capacity

PART I (cont.) Vendor: <u>SCHETKY NW SALES</u> THOMAS BUILT BUS

ITEM	SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
	ADDITIONAL REQUIREMENTS—CHASSIS AND BODY	
Line Setting Ticket	Legible copy of manufacturer's Line Setting Ticket will be delivered with each vendor's packet at the time of delivery of the bus.	Check if as specified ⊠
Owner's/Operator's Handbook	One copy of the chassis manufacturer's owner's/operator's handbook or manual will be furnished with each bus at time of delivery.	Check if as specified ⊠
Repair Manuals	A complete set of chassis, engine, transmission, and body repair manuals, including wiring diagram for all components, will be made available at time of delivery, with instructions available on accessing repair materials.	Check if as specified ⊠
Service and Cleaning	<ul> <li>Cleaning and service by vendor prior to delivery will include:</li> <li>Chassis lubrication.</li> <li>Check fluid levels: verify all are at recommended full levels.</li> <li>Cooling system protected at -20°F.</li> <li>Interior and exterior will be clean (including glass).</li> <li>All systems (electric, air, hydraulic, mechanical, and manual) be inspected to ensure proper operation at time of delivery.</li> <li>All components and accessories will be installed and operational at time of delivery.</li> </ul>	Check if as specified ⊠
Warranty	A complete copy of all warranty agreements will be furnished at time of delivery.	Check if as specified ⊠

Washington Office of Superintendent of PUBLIC INSTRUCTION

2024-2025

#### STUDENT TRANSPORTATION Old Capitol Building PO BOX 47200 Olympia, WA 98504-7200 (360) 725-6120 TTY (360) 664-3631

### VEHICLE DATA SHEET AND OFFICIAL PRICE QUOTATION TYPE D—84 PASSENGER, REAR ENGINE

VENDOR'S COMPANY NAME SCHETKY NW SALES INC	REPRESENTATIVE'S NAME SCOTT MEYER	TELEPHONE NUMBER 509-579-6267
ADDRESS 8430 NE LOMBARD ST	Estimated delivery date to school district from time purchase order is received: 240-260	
PORTLAND, OR 97220	Firm where engine and chassis can be serviced or repaired, and parts obtained:	
	SCHETKY	_
	Firm where body can be serviced or repaired, and parts obtained	ed: <u>SCHETKY</u>

BODY					
MAKE THOMAS MODEL	YEAR	,	Years <u>1</u> Miles <u>UNLIM</u>	Inside measurement from rear of stepwell to appropriate point at	Equipped seating capacity: w/o lift <u>78</u> w/lift <u>N/A</u>
370DS	2025	Seat color: Floor color:		rear of passenger seating area: w/o lift <u>396.5</u> w/lift <u>N/A</u>	Overall vehicle length (inches): w/o lift <u>469.9</u> w/lift <u>N/A</u>

CHASSIS			ENGINE		
make THOMAS		Warranty: Years <u>1</u> Miles <u>UNLIM</u>	MANUFACTURER CUMMINS	Torque: <u>660</u> @ <u>1600</u> RPM           H.P.: <u>280</u> @ <u>2400</u> RPM	
MODEL 370DS	YEAR 2025	Wheelbase: 267	MODELYEARB6.7L2025	C.I.D. : <u>6.7L</u> Fuel type : <u>DIESEL</u>	
	TRANSMISSION		Warranty: Years <u>5</u>	Battery type/grp: <u>31</u>	
MANUFACTURER ALLISON		Speeds forward: 5	Miles <u>100,000</u>	Number batteries: <u>2</u>	
MODEL 3000PTS		Warranty: Years <u>5</u> Miles <u>UNLIM</u>	Number of cylinders: <u>6</u> Inline <u>X</u> V-type	_Total CCA: <u>1900</u>	

#### **QUOTED PRICE**

DATE

Quoted price is based upon payment within 30 days after delivery to the school district (without sales tax).

Bid—w/o lift \$ <u>197,598.00</u>

Bid—w/lift \$ NO BID

VENDOR REPRESENTATIVE'S SIGNATURE

Scott Meyer

08/06/2024

PART II Vendor: <u>SCHETKY NW</u> <u>SALES</u> <u>THOMAS BUILT BUS</u>

## State Price Quote Specification DISTRICT-SUPPORTED OPTIONS C60 C77 D60 XD84

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.		
Activity	2-passenger position seats with lap-shoulder belts in all passenger	Passenger Capacity <u>52</u>		
Securement Seating	positions.	Cost \$ <u>650.00 PER SEAT, R</u>	EPLACE STD SEAT	
Air Conditioning	To cool passenger compartment as required in the Washington State	Mfr. CARRIER 104K BTU		
All Conditioning	School Bus Specifications manual.	Cost \$ <u>17,250.00</u>		
Alternate Fuel	Must comply with power and gradeability formula. Refer to	Mfr. <u>N/A</u>		
	Washington State School Bus Specifications manual. Must comply with	□ Cost \$		
Electric	all the requirements of FMVSS No. 305.	Electric Cost \$		
		Cost \$ <u>1,650.00</u>	Capacity <u>270AMP</u>	
Alternator	Available options.	Cost \$ <u>2,225.00</u>	Capacity <u>320AMP</u>	
		Cost \$	Capacity	
Anti-spray Device	Rubber fender extenders.	Type C: Cost \$ <u>195.00</u>		
And opidy Device		Type D: Cost \$ <u>375.00</u>		
Back-up Alarm	Must meet state specification.	Mfr. THOMAS		
Back-up Alaim		Cost \$ <u>175.00</u>		
Brakes	4-wheel hydraulic disk brake.	Cost \$ <u>N/A</u>	Deduct \$ <u>N/A</u>	
	Air, Drum or Disc. Refer to Washington State School Bus	Disc Cost \$ <u>4,350.00</u>	Disc Deduct \$ <u>N/A</u>	
Brakes	Specifications manual.	Drum Cost \$ <u>INCLUDED</u>	Drum Deduct \$ <u>N/A</u>	
Color	Exterior white roof.	Cost \$ <u>790.00</u>	·	
Door Locks	Vandal lock system on all exterior doors.	Cost \$ <u>350.00</u>	_	
		Non-Air	Air	
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Mfr. <u>N/A</u>	Mfr. NATIONAL	
		Cost \$ INCLUDED	Cost \$ INCLUDED	
Fire Suppression	Fire Suppression Jomarr VT-6-E-NAF, or equal engine compartment fire suppression			
System	system of appropriate size to be installed according to manufacturer recommendation.	Cost \$ <u>6,300.00</u>		
Floor Color	Nonstandard color.	Cost \$ <u>950.00</u>		

## State Price Quote Specification DISTRICT-SUPPORTED OPTIONS C60 C77 D60 MD84

PART II (cont.) Vendor: <u>SCHETKY NW</u> <u>SALES</u> <u>THOMAS BUILT BUS</u>

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.		
Fuel Tank	Larger fuel capacity (Diesel only).	Size: INCLUDED Cost \$		
Fuel Tank	Larger fuel capacity (Propane only).	Size: N/A         Cost \$		
Headlights	Halogen.	Cost \$ INCLUDED		
Headlights	L.E.D.	Cost \$ <u>950.00</u>		
Heater (Auxiliary water)	Auxiliary fuel-fired heating systems. Refer to Washington State School Bus Specifications Manual, page 27.	Brand: <u>WEBASTO</u> Model: <u>PR090</u> Cost \$ <u>5,500.00</u>		
Noise Reduction	Exceeding minimum specifications.	Driver compartmentCost \$ 250.00Engine compartmentCost \$ INCLUDEDFull acoustical headlinerCost \$ 990.00		
Retarder	Manufacturer's standard.	Driveline         □         Cost \$           Exhaust         ⊠         Cost \$ <u>175.00</u> Transmission         □         Cost \$		
Seat Belt Ready Seat	3-passenger position seat with securement belts.	Cost \$ <u>1,225.00</u>		
Seating System	Identical, non-lift bus with lap-shoulder seat belt system installed in all positions.	2 by 2 Cost \$ <u>12,718.00</u> Capacity <u>44</u> 3 by 2 Cost \$ <u>12,718.00</u> Capacity <u>44</u> 3 by 3 Cost \$ <u>16,184.00</u> Capacity <u>84</u>		

## State Price Quote Specification DISTRICT-SUPPORTED OPTIONS C60 C77 D60 MD84

PART II (cont.) Vendor: <u>SCHETKY NW</u> <u>SALES</u> <u>THOMAS BUILT BUS</u>

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.		
	· · · · · · · · · · · · · · · · · · ·	Left side 21.4	cubic feet.	
Storage		Cost \$ <u>1,375.00</u>		
		Right-side 21.4	cubic feet.	
Compartments	Largest available for unit bid.	Cost \$ <u>1,375.00</u>		
		Push-thru <u>129</u>	cubic feet.	
		Cost \$ <u>5,600.00</u>		
		Mfr. <u>THOMAS</u>		
Strobe Light	Exterior roof mounted white strobe light.	Model No. <u>DOUBLE FLA</u>	SH	
		Cost \$ <u>295.00</u>		
	Electronic system to insure driver post-trip inspection of passenger compartment.	Mfr. THOMAS		
Student Protection		Model No. PASS-ADVISORY		
System—Installed		Cost \$ <u>390.00</u>		
Suspension	Air ride (Air brake system only).	Front	Rear	
Suspension	All fide (All blake system only).	Cost \$ <u>N/A</u>	Cost \$ <u>4,025.00</u>	
Toolbox	Interior, manufacturer standard.	Cost \$ <u>85.00</u>	Deduct \$ <u>N/A</u>	
Traction Device	Automatic chains.	Mfr. <u>ON-SPOT</u>		
Traction Device	Automatic chains.	Cost \$ <u>4,950.00</u>		
Traction Device	Sanders	Capacity <u>158LB</u>		
Traction Device	Sanders.	Cost \$ <u>6,100.00</u>		
		Mfr. INCLUDED		
Transmission	Automatic—Allison, PTS 3000 or equal.	Model No.		
Vehicle Securement System	Must meet state specification.	Mfr. <u>SAFETY BRAKE</u>	Cost \$ <u>2,150.00</u>	

## State Price Quote Specification DISTRICT-SUPPORTED OPTIONS C60 C77 D60 MD84

PART II (cont.) Vendor: <u>SCHETKY NW</u> <u>SALES</u> <u>THOMAS BUILT BUS</u>

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.		VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Video Camera		Mfr. <u>SEON</u>		
Systems—	Digital audio/video system for monitoring the passenger compartment with more than two cameras.	Model No. <u>DH</u>		
Installed	comparament war more than two cameras.	Cost \$ <u>4,230.00</u> ⊢	low many cameras <u>3</u>	
		Stand Alone System	Added to Interior System	
Video Camera		Mfr. <u>SEON</u>	Mfr. <u>SEON</u>	
Systems—Stop Sign Camera—	Must meet state specification.	Model No. <u>DH</u>	Model No. <u>DH</u>	
Installed		Cost \$ <u>4,780.00</u>	Cost \$ <u>705.00</u>	
		How many cameras <u>4</u>	How many cameras <u>1</u>	
Warning Light	16 light monitoring system.	Incandescent	LED Lights	
Monitor		Cost \$ <u>N/A</u>	Cost \$ <u>750.00</u>	
Additional		Mfr. <u>N/A</u>		
Wheelchair/Occup ant Tie-down	Must meet state specification.	Model No.		
System—Installed		Cost per station \$		
•		Side Cost \$ <u>1,500.00</u>		
Windows	Laminated passenger-compartment side or rear glass.	Rear Cost \$ INCLUDED INSIDE COST		
		Both Cost \$ <u>1,500.00</u>	Both Cost \$ <u>1,500.00</u>	
Windows	Tinted.	Cost \$ <u>750.00</u>		
Windows	Thermal pane, left of driver and service door.	Cost \$ 895.00		