



State Price Quote Specification
**TYPE C60—BID AS 48 PASSENGER,
ELECTRIC**

PART I

Vendor: RWC Group

Use this document to bid both non-lift and lift buses for 35-60 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.
Seating Capacity	48 passenger based upon an average center-to-center seat spacing of at least 27.5".	Capacity w/o lift <u>48</u> Capacity w/lift <u>36+1</u>
Auxiliary Fans	2 fans, 6" maximum, mounted to right and left windshield and service door.	Mfr. <u>Bergstrom</u>
Axle—Front	9,000 lb. minimum.	Mfr. <u>Meritor</u> Capacity <u>10,000</u>
Axle—Rear	19,000 lb. minimum.	Mfr. <u>Dana</u> Capacity <u>21,000</u>
Axle Oil Seals	Front and rear oil bath, or maintenance free sealed greased bearings.	Mfr. <u>Conmet Preset</u>
Axle Ratio	Must comply with power and gradeability formula. Refer to Washington State School Bus Specifications Manual.	Mfr. <u>Dana</u> Capacity <u>5.57</u>
Back-up Lights	All required backup lights to be LED (Light Emitting Diode). Refer to Washington State School Bus Specification's Manual.	Round: ☒ Diameter <u>7"</u> Other: ☐ Square inches _____
Battery(ies) Low Voltage	1200 CCA 12 volt minimum to be mounted in body battery compartment w/o lift. 1400 CCA 12 volt minimum to be mounted in body battery compartment w/lift.	Number of batteries <u>2</u> CCA <u>2300</u>
Battery(ies) Propulsion	Battery propulsion must meet a minimum of 130 kWh.	Number of batteries <u>4</u> kWh <u>210</u>

State Price Quote Specification
**TYPE C60—BID AS 48 PASSENGER,
 ELECTRIC**

PART I (cont.)
 Vendor: RWC Group

Use this document to bid both non-lift and lift buses for 35-60 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.	
Battery Compartment	Battery storage tray must be large enough to accommodate batteries as specified in chassis section.	☐ Swing out	☒ Roll out
Brakes	Air: Drum or Disc. Refer to Washington State School Bus Specifications Manual.	Disc Front ☒ Drum Front ☐ Size Front <u>22.5</u>	Rear ☒ Rear ☐ Rear <u>22.5</u>
Door, Service	Power operated.	☐ Air ☒ Electric ☐ Other	☐ Folding ☒ Split, Outward opening ☐ Other
Heaters	Minimum of 3 heaters; 1 front, 1 center, 1 rear. Shutoff valves at engine for all heaters. Two-speed motors.	Front B.T.U. <u>41,000</u> Center B.T.U. <u>84,500</u> Rear B.T.U. <u>84,500</u> Total B.T.U. <u>210,000</u>	
Hood	Tilt.	☒ Fiberglass ☐ Metal	
Lights	LED (Light Emitting Diode). Includes Clearance Lights, Stop Lights—7", Taillights, Turn Signals, Eight-Light System, and Dome-Light System.	Check if as specified ☒ If not, explain. _____	
Motor	190 H.P. minimum.	Engine Mfr. <u>Dana TM4 Sumo</u> Model <u>HV2200-6P</u> Net torque <u>990</u> @ <u>1000</u> R.P.M. Net H.P. <u>255</u> @ <u>1000</u> R.P.M.	
P.A. System	AM/FM/PA radio with 2 interior and 1 exterior speakers.	Mfr. <u>International</u> Model No. <u>4275485C91</u>	

State Price Quote Specification
**TYPE C60—BID AS 48 PASSENGER,
 ELECTRIC**

Use this document to bid both non-lift and lift buses for 35-60 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.
Seat Spacing	To permit specified passenger capacity based on an average center-to-center seat spacing of at least 27.5".	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: w/o lift <u>270.9</u> w/lift <u>270.9</u> Mfg.'s C/C seat measurement of vehicle (inches): w/o lift <u>31.35</u> w/lift <u>31.21</u>
Steering Wheel	Tilt and telescoping column.	Check if as specified ☒
Step Tread	Studded or pebbled top tread covering.	Mfr. <u>Koroseal</u>
Tires	6 first quality, radial ply.	Mfr. <u>Hankook</u> Size <u>255/70</u> Load range <u>H</u>
Toolbox	Exterior, manufacturer standard.	Size (cubic feet) <u>2.88</u>
Two-way Communications	45-watt, VHF, mil. spec.	Mfr. <u>ICOM</u> Model No. <u>F-5011</u>
Wheels	6 to be compatible with tire size.	Size <u>22.5</u> Rim width <u>8.25</u>
SPECIAL NEEDS REQUIREMENTS—CHASSIS AND BODY		
Wheelchair Lift—Installed	Must meet state specification. Platform shall be a minimum of 32" x 52".	Mfr. <u>Braun</u> Model No. <u>NL919FIB</u>
Wheelchair/ Occupant Tie-down System—Installed	Must meet state specification.	Mfr. <u>Q Straint</u> Model No. <u>Q-8107-A1-L2</u>

State Price Quote Specification
**TYPE C60—BID AS 48 PASSENGER,
ELECTRIC**

Use this document to bid both non-lift and lift buses for 35-60 capacity.

PART I (cont.)
Vendor: RWC Group

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.
ADDITIONAL REQUIREMENTS—CHASSIS AND BODY		
Line Setting Ticket	Legible copy of manufacturer's Line Setting Ticket will be delivered with each vendor's packet at the time of delivery of the bus.	Check if as specified ☒
Owner's/Operator's Handbook	One copy of the chassis manufacturer's owner's/operator's handbook or manual will be furnished with each bus at time of delivery.	Check if as specified ☒
Repair Manuals	A complete set of chassis, engine, transmission, and body repair manuals, including wiring diagram for all components, will be made available at time of delivery, with instructions available on accessing repair materials.	Check if as specified ☒
Service and Cleaning	Cleaning and service by vendor prior to delivery will include: • Chassis lubrication. • Check fluid levels: verify all are at recommended full levels. • Cooling system protected at -20°F. • Interior and exterior will be clean (including glass). • All systems (electric, air, hydraulic, mechanical, and manual) be inspected to ensure proper operation at time of delivery. • All components and accessories will be installed and operational at time of delivery.	Check if as specified ☒
Warranty	A complete copy of all warranty agreements will be furnished at time of delivery.	Check if as specified ☒



Washington Office of Superintendent of
PUBLIC INSTRUCTION
2026-2027

STUDENT TRANSPORTATION
Old Capitol Building
PO BOX 47200
Olympia, WA 98504-7200
(360) 725-6120 TTY (360) 664-3631

VEHICLE DATA SHEET AND OFFICIAL PRICE QUOTATION TYPE C60— BID AS 48 PASSENGER ELECTRIC

VENDOR'S COMPANY NAME RWC Group		REPRESENTATIVE'S NAME Tom Hartman		TELEPHONE NUMBER 602-377-4401	
ADDRESS 600 North 75 th Avenue Phoenix, AZ 85043		Estimated delivery date to school district from time purchase order is received: <u>6-8 mos</u> Firm where engine and chassis can be serviced or repaired, and parts obtained: <u>Any IC or International Dealer</u> Firm where body can be serviced or repaired, and parts obtained: <u>RWC Group</u>			
BODY					
MAKE IC Corporation		Warranty: Years <u>3</u> Miles <u>36,000</u>		Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: w/o lift <u>270.9</u> w/lift <u>270.9</u>	
MODEL PB11E		YEAR 2028		Equipped seating capacity: w/o lift <u>48</u> w/lift <u>36+1</u> Overall vehicle length (inches): w/o lift <u>384.9</u> w/lift <u>384.9</u>	
CHASSIS					
MAKE IC Corporation		Warranty: Years <u>5</u> Miles <u>Unlimit</u>		MOTOR	
MODEL PB11E		YEAR 2028		MANUFACTURER Dana TM4 Sumo	
		Wheelbase: <u>218</u>		Torque: <u>990</u> @ <u>1000</u> RPM H.P.: <u>255</u> @ <u>1000</u> RPM	
				MODEL HV2200-6P	
				YEAR 2027	
				C.I.D. or Liters: _____ Fuel type: <u>Electric</u>	
BATTERIES					
12 Volt		Propulsion			
Battery type/grp: <u>31</u> <u>31</u>		Number batteries: <u>4</u>			
Number batteries: <u>2</u>		Total kWh: <u>210</u>			
Total CCA: <u>2300</u>		Warranty: Years <u>5</u> Miles <u>100,000</u>			
QUOTED PRICE					
Quoted price is based upon payment within 30 days after delivery to the school district (without sales tax).					
Electric Bid—w/o lift \$ <u>440,997</u> Electric Bid—w/lift \$ <u>448,912</u>					
VENDOR REPRESENTATIVE'S SIGNATURE <u>Tom Hartman</u>				DATE <u>7-31-26</u>	

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

Vendor: RWC Group

☒ **C60** ☐ **D84 – ELECTRIC**

Use this document to bid both non-lift and lift buses.

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Activity Securement Seating	2-passenger position seats with lap-shoulder belts in all passenger positions.	Passenger Capacity <u>32</u> Cost \$ <u>15,800</u>	
Air Conditioning	To cool passenger compartment as required in the Washington State School Bus Specifications manual.	Mfr. <u>TransAir</u> Cost \$ <u>28,000</u>	
Anti-spray Device	Rubber fender extenders.	Type C: Cost \$ <u>Standard</u> Type D: Cost \$ <u>NA</u>	
Back-up Alarm	Must meet state specification.	Mfr. <u>Ecco</u> Cost \$ <u>Standard</u>	
Brakes	4-wheel hydraulic disk brake.	Cost \$ <u>NA</u>	Deduct \$ <u>NA</u>
Brakes	Air, Drum or Disc. Refer to Washington State School Bus Specifications manual.	Disc Cost \$ <u>Standard</u> Drum Cost \$ <u>NA</u>	Disc Deduct \$ <u>NA</u> Drum Deduct \$ <u>NA</u>
Color	Exterior white roof.	Cost \$ <u>776</u>	
Door Locks	Vandal lock system on all exterior doors.	Cost \$ <u>350</u>	
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Non-Air Mfr. <u>Magnum</u> Cost \$ <u>350</u>	Air Mfr. <u>Sears Atlas II</u> Cost \$ <u>1,200</u>
Fire Suppression System	Jomarr VT-6-E-NAF, or equal engine compartment fire suppression system of appropriate size to be installed according to manufacturer recommendation.	Mfr. <u>NA</u> Cost \$ <u>NA</u>	
Floor Color	Nonstandard color.	Cost \$ <u>419</u>	
Headlights	Halogen.	Cost \$ <u>NA</u>	
Headlights	L.E.D.	Cost \$ <u>Standard</u>	

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☒ **C60** ☐ **D84 – ELECTRIC**

Use this document to bid both non-lift and lift buses.

PART II (cont.)

Vendor: RWC Group

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
Heater (Auxiliary water)	Auxiliary fuel-fired heating systems. Refer to Washington State School Bus Specifications Manual, page 27.	Brand: <u>Webasto</u> Model: <u>Pro 90</u> Cost \$ <u>5,300</u>
Noise Reduction	Exceeding minimum specifications.	Driver compartment Cost \$ <u>150</u> Engine compartment Cost \$ <u>NA</u> Full acoustical headliner Cost \$ <u>Standard</u>
Retarder	Manufacturer's standard.	Driveline ☐ Cost \$ <u>NA</u> Exhaust ☐ Cost \$ <u>NA</u> Transmission ☐ Cost \$ <u>NA</u>
Seat Belt Ready Seat	3-passenger position seat with securement belts.	Cost \$ <u>1,056</u>
Seating System	Identical, non-lift bus with lap-shoulder seat belt system installed in all positions.	2 by 2 Cost \$ <u>15,800</u> Capacity <u>32</u> 3 by 2 Cost \$ <u>NA</u> Capacity <u>NA</u> 3 by 3 Cost \$ <u>16,800</u> Capacity <u>48</u>
Storage Compartments	Largest available for unit bid.	Left side <u>NA</u> cubic feet. Cost \$ <u>NA</u> Right-side <u>NA</u> cubic feet. Cost \$ <u>NA</u> Push-thru <u>NA</u> cubic feet. Cost \$ <u>NA</u>
Strobe Light	Exterior roof mounted white strobe light.	Mfr. <u>Ecco</u> Model No. <u>6550C</u> Cost \$ <u>217</u>

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☒ **C60** ☐ **D84 – ELECTRIC**

Use this document to bid both non-lift and lift buses.

PART II (cont.)

Vendor: RWC Group

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Student Protection System—Installed	Electronic system to insure driver post-trip inspection of passenger compartment.	Mfr. <u>IC Corporation</u> Model No. <u>Leave no student behind</u> Cost \$ <u>Standard</u>	
Suspension	Air ride (Air brake system only).	Front	Rear
		Cost \$ <u>NA</u>	Cost \$ <u>Standard</u>
Toolbox	Interior, manufacturer standard.	Cost \$ <u>117</u>	Deduct \$ <u>NA</u>
Traction Device	Automatic chains.	Mfr. <u>On Spot</u> Cost \$ <u>5,868</u>	
Traction Device	Sanders.	Capacity <u>10</u> Gal Cost \$ <u>5,784</u>	
Vehicle Securement System	Must meet state specification.	Mfr. <u>Bendix Intellipark</u>	Cost \$ <u>500</u>
Video Camera Systems—Installed	Digital audio/video system for monitoring the passenger compartment with more than two cameras.	Mfr. <u>Seon</u> Model No. <u>TH4</u> Cost \$ <u>4,029</u> How many cameras <u>3</u>	
Video Camera Systems—Stop Sign Camera—Installed	Must meet state specification.	Stand Alone System	Added to Interior System
		Mfr. <u>Seon</u>	Mfr. <u>Seon</u>
		Model No. <u>TH4</u>	Model No. <u>TH4</u>
		Cost \$ <u>3,124</u>	Cost \$ <u>1,191</u>
		How many cameras <u>1</u>	How many cameras <u>1</u>
Warning Light Monitor	16 light monitoring system.	Incandescent	LED Lights
		Cost \$ <u>NA</u>	Cost \$ <u>386</u>

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

Vendor: RWC Group

☒ **C60** ☐ **D84 – ELECTRIC**

Use this document to bid both non-lift and lift buses.

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
Additional Wheelchair/Occupant Tie-down System—Installed	Must meet state specification.	Mfr. <u>Q Straint</u>
		Model No. <u>Q-8107-A1-L2</u>
		Cost per station \$ <u>2,700</u>
Windows	Laminated passenger-compartment side or rear glass.	Side Cost \$ <u>547</u>
		Rear Cost \$ <u>242</u>
		Both Cost \$ <u>1,337</u>
Windows	Tinted.	Cost \$ <u>524</u>
Windows	Thermal pane, left of driver and service door.	Cost \$ <u>450</u>