

State Price Quote Specification
**TYPE D84—BID AS 78 PASSENGER
DIESEL**

PART I

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

Use this document to bid both non-lift and lift buses for 61–84 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.	
Seating Capacity	78 passenger based upon maximum seat spacing allowed in accordance with FMVSS 222.	Capacity w/o lift <u>78</u>	
		Capacity w/lift <u>N/A</u>	
Alternator	240 amp minimum. Lift-equipped or air-conditioned. Manufacturer recommended capacity.	Mfr. <u>LEECE NEVILLE</u> Max. amps output w/o lift or A.C. <u>240</u> Max. amps output w/lift or A.C. <u>N/A</u>	
Auxiliary Fans	2 fans, 6" maximum, mounted to right and left windshield and service door.	Mfr. <u>BERGSTROM</u>	
Axle—Front	13,200 lb. minimum.	Mfr. <u>DETROIT</u> Capacity <u>13,200</u>	
Axle—Rear	19,000 lb. minimum.	Mfr. <u>DETROIT</u> Capacity <u>19,000</u>	
Axle Oil Seals	Front and rear oil bath, or maintenance free sealed greased bearings.	Mfr. <u>CR</u>	
Axle Ratio	Must comply with power and gradeability formula. Refer to Washington State School Bus Specifications Manual.	Ratio <u>5.13</u>	
Back-up Lights	All required backup lights to be LED (Light Emitting Diode). Refer to Washington State School Bus Specification's Manual.	Round: ☐ Diameter _____ Other: ☒ Square inches <u>22</u>	
Battery(ies)	1200 CCA 12 volt minimum to be mounted in body battery compartment w/o lift. 1400 CCA 12 volt minimum to be mounted in body battery compartment w/lift.	Size/group w/o lift <u>31</u> CCA <u>2850</u> Size/group w/lift <u>N/A</u> CCA <u>N/A</u>	
Battery Compartment	Battery storage tray must be large enough to accommodate batteries as specified in chassis section.	☐ Swing out	☒ Roll out

State Price Quote Specification
**TYPE D84—BID AS 78 PASSENGER
DIESEL**

PART I (cont.)

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

Use this document to bid both non-lift and lift buses for 61–84 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.
Brakes	Air: Drum or Disc. If Drum, minimum 16.5" x 5" front, minimum 16.5" x 7" rear. Refer to Washington State School Bus Specifications Manual.	Disc Front ☐ Rear ☐ Drum Front ☒ Rear ☒ Size <u>16.5x5</u> Rear <u>15.5x7</u>
Door, Service	Power operated.	☒ Air ☐ Folding ☐ Electric ☒ Split, Outward opening ☐ Other ☐ Other
Engine	Diesel—210 H.P. minimum.	Engine mfr. <u>CUMMINS</u> Model or liters <u>B6.7L</u> Net torque <u>600</u> @ <u>1600</u> R.P.M Net H.P. <u>220</u> @ <u>2400</u> R.P.M Location: Rear ☐ Forward ☒
Engine Heater	Engine manufacturers recommended in-block heater.	Watts <u>750</u> Volts <u>115</u> Mfr. <u>PHILLIPS</u>
Engine Temperature	To be controlled electronically, by fan clutch/drive, or shutters.	Mfr. <u>EATON</u> ☐ Electronic ☒ Fan clutch ☐ Shutters
Fuel Tank	Diesel—100-gallon minimum.	Capacity <u>100 GALLONS</u>

State Price Quote Specification
**TYPE D84—BID AS 78 PASSENGER
 DIESEL**

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

Use this document to bid both non-lift and lift buses for 61–84 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.
Heaters	Minimum of 3 heaters; 1 front, 1 center, 1 rear. Shutoff valves at engine for all heaters. Two-speed motors. Must include recirculating pump.	Front B.T.U. <u>90,000</u> Center B.T.U. <u>50,000</u> Rear B.T.U. <u>50,000</u> Total B.T.U. <u>190,000</u>
Lights	LED (Light Emitting Diode). Includes Clearance Lights, Stop Lights—7", Taillights, Turn Signals, Eight-Light System, and Dome-Light System.	Check if as specified ☒ If not, explain. _____
P.A. System	AM/FM/PA radio with 2 interior and 1 exterior speakers.	Mfr. <u>DELPHI</u> Model No. <u>DEA700</u>
Seat Spacing	78 passenger based upon maximum seat spacing allowed in accordance with FMVSS 222.	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: w/o lift <u>407</u> w/lift <u>N/A</u> Mfg.'s C/C seat measurement of vehicle (inches): w/o lift <u>30</u> w/lift <u>N/A</u>
Steering Wheel	Tilt and telescoping column.	Check if as specified ☒
Step Tread	Studded or pebbled top tread covering.	Mfr. <u>KOROSEAL</u>
Tires	6 first quality, radial ply.	Mfr. <u>HANKOOK AH37</u> Size <u>11R22.5</u> Load range <u>G</u>
Toolbox	Exterior, manufacturer standard.	Size (cubic feet) <u>8.9</u>
Transmission	Automatic—Allison, PTS 2500 or equal.	Mfr. <u>ALLISON</u> Model No. <u>2500PTS</u> Net input torque <u>600</u> Net input H.P. <u>220</u>

PART I (cont.)
State Price Quote Specification
**TYPE D84—BID AS 78 PASSENGER
DIESEL**

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

Use this document to bid both non-lift and lift buses for 61–84 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.
Two-way Communications	45-watt, VHF, mil. spec.	Mfr. <u>MOTOROLA</u> Model No. <u>CM300D</u>
Wheels	6 to be compatible with tire size.	Size <u>22.5"</u> Rim width <u>8.25"</u>
	SPECIAL NEEDS REQUIREMENTS—CHASSIS AND BODY	
Wheelchair Lift—Installed	Must meet state specification. Platform shall be a minimum of 32" x 52".	Mfr. <u>N/A</u> Model No. <u>N/A</u>
Wheelchair/ Occupant Tie-down System—Installed	Must meet state specification.	Mfr. <u>N/A</u> Model No. <u>N/A</u>

State Price Quote Specification
**TYPE D84—BID AS 78 PASSENGER
 DIESEL**

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

Use this document to bid both non-lift and lift buses for 61–84 capacity.

ITEM	STATE-SUPPORTED SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the state cost.
	ADDITIONAL REQUIREMENTS—CHASSIS AND BODY	
Line Setting Ticket	Legible copy of manufacturer's Line Setting Ticket will be delivered with each vendor's packet at the time of delivery of the bus.	Check if as specified ☒
Owner's/Operator's Handbook	One copy of the chassis manufacturer's owner's/operator's handbook or manual will be furnished with each bus at time of delivery.	Check if as specified ☒
Repair Manuals	A complete set of chassis, engine, transmission, and body repair manuals, including wiring diagram for all components, will be made available at time of delivery, with instructions available on accessing repair materials.	Check if as specified ☒
Service and Cleaning	Cleaning and service by vendor prior to delivery will include: • Chassis lubrication. • Check fluid levels: verify all are at recommended full levels. • Cooling system protected at -20°F. • Interior and exterior will be clean (including glass). • All systems (electric, air, hydraulic, mechanical, and manual) be inspected to ensure proper operation at time of delivery. • All components and accessories will be installed and operational at time of delivery.	Check if as specified ☒
Warranty	A complete copy of all warranty agreements will be furnished at time of delivery.	Check if as specified ☒



Washington Office of Superintendent of
PUBLIC INSTRUCTION
2026-2027

STUDENT TRANSPORTATION
Old Capitol Building
PO BOX 47200
Olympia, WA 98504-7200
(360) 725-6120 TTY (360) 664-3631

VEHICLE DATA SHEET AND OFFICIAL PRICE QUOTATION TYPE D84—BID AS 78 PASSENGER (DIESEL)

VENDOR'S COMPANY NAME SCHETKY NW SALES, INC.		REPRESENTATIVE'S NAME SCOTT MEYER	TELEPHONE NUMBER 509-579-6267
ADDRESS 8430 NE LOMBARD ST. PORTLAND, OR. 97220		Estimated delivery date to school district from time purchase order is received: <u>240-260</u> Firm where engine and chassis can be serviced or repaired, and parts obtained: <u>SCHETKY</u> Firm where body can be serviced or repaired, and parts obtained: <u>SCHETKY</u>	

BODY				
MAKE THOMAS BUILT BUS		Warranty: Years <u>3</u> Miles <u>50,000</u> Seat color: <u>GREY</u> Floor color: <u>GREY</u>	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: w/o lift <u>407"</u> w/lift <u>N/A</u>	Equipped seating capacity: w/o lift <u>78</u> w/lift <u>N/A</u> Overall vehicle length (inches): w/o lift <u>457.1"</u> w/lift <u>N/A</u>
MODEL 381ES	YEAR 2027			

CHASSIS			ENGINE		
MAKE THOMAS		Warranty: Years <u>3</u> Miles <u>50,000</u>	MANUFACTURER CUMMINS		Torque: <u>600</u> @ <u>1600</u> RPM H.P.: <u>220</u> @ <u>2400</u> RPM
MODEL CHSY	YEAR 2027		Wheelbase: <u>212"</u>	MODEL B6.7L	YEAR 2027
TRANSMISSION			Warranty: Years <u>5</u> Miles <u>100,000</u>		Battery type/grp: <u>31</u> <u>N/A</u>
MANUFACTURER ALLISON		Speeds forward: <u>6</u>	Number of cylinders: <u>6</u> Inline <u>X</u> V-type <u> </u>		Number batteries: <u>3</u> <u>N/A</u>
MODEL 2500PTS		Warranty: Years <u>5</u> Miles <u>UNLIMITED</u>			Total CCA: <u>2850</u> <u>N/A</u>

QUOTED PRICE	
Quoted price is based upon payment within 30 days after delivery to the school district (without sales tax).	
Diesel Bid—w/o lift \$ <u>193,507.00</u> Diesel Bid—w/lift \$ <u>NO BID</u>	
VENDOR REPRESENTATIVE'S SIGNATURE <u> </u>	DATE <u>7/31/0226</u>

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

☐ C60 ☐ C77 ☐ D60 ☒ D84

Use this document to bid both non-lift and lift buses.

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Activity Securement Seating	2-passenger position seats with lap-shoulder belts in all passenger positions.	Passenger Capacity <u>52</u> Cost \$ <u>650.00 PER SEAT, REPLACE STD. SEAT</u>	
Air Conditioning	To cool passenger compartment as required in the Washington State School Bus Specifications manual.	Mfr. <u>CARRIER AC-IW10/IW1 115K BTU</u> Cost \$ <u>17,250.00</u>	
Alternator	Available options.	Cost \$ <u>1650.00</u> Capacity <u>270A</u> Cost \$ <u>2,225.00</u> Capacity <u>320A</u> Cost \$ <u>N/A</u> Capacity <u>N/A</u>	
Anti-spray Device	Rubber fender extenders.	Type C: Cost \$ <u>195.00</u> Type D: Cost \$ <u>375.00</u>	
Back-up Alarm	Must meet state specification.	Mfr. <u>ECCO 850N-TB2</u> Cost \$ <u>175.00</u>	
Brakes	4-wheel hydraulic disk brake.	Cost \$ <u>N/A</u>	Deduct \$ <u>N/A</u>
Brakes	Air, Drum or Disc. Refer to Washington State School Bus Specifications manual.	Disc Cost \$ <u>4,350.00</u> Drum Cost \$ <u>INCLUDED</u>	Disc Deduct \$ <u>N/A</u> Drum Deduct \$ <u>N/A</u>
Color	Exterior white roof.	Cost \$ <u>790.00</u>	
Door Locks	Vandal lock system on all exterior doors.	Cost \$ <u>350.00</u>	
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Non-Air	Air
		Mfr. <u>NATIONAL</u>	Mfr. <u>NATIONAL</u>
		Cost \$ <u>N/A</u>	Cost \$ <u>INCLUDED</u>
Fire Suppression System	Jomarr VT-6-E-NAF, or equal engine compartment fire suppression system of appropriate size to be installed according to manufacturer recommendation.	Mfr. <u>FOGMAKER</u> Cost \$ <u>15,639.00</u>	

PART II (cont.)

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C60 ☐ C77 ☐ D60 ☒ D84

Use this document to bid both non-lift and lift buses.

Vendor: SCHETKY NW
SALES
THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Floor Color	Nonstandard color.	Cost \$ <u>950.00</u>	
Fuel Tank	Larger fuel capacity (Diesel only).	Size: <u>N/A</u>	Cost \$ <u>N/A</u>
Fuel Tank	Larger fuel capacity (Propane only).	Size: <u>N/A</u>	Cost \$ <u>N/A</u>
Headlights	Halogen.	Cost \$ <u>INCLUDED</u>	
Headlights	L.E.D.	Cost \$ <u>1408.00</u>	
Heater (Auxiliary water)	Auxiliary fuel-fired heating systems. Refer to Washington State School Bus Specifications Manual, page 27.	Brand: <u>WEBASTO</u>	Model: <u>PRO90</u> Cost \$ <u>5,550.00</u>
Noise Reduction	Exceeding minimum specifications.	Driver compartment	Cost \$ <u>250.00</u>
		Engine compartment	Cost \$ <u>INCLUDED</u>
		Full acoustical headliner	Cost \$ <u>INCLUDED</u>
Retarder	Manufacturer's standard.	Driveline ☐	Cost \$ _____
		Exhaust ☒	Cost \$ <u>175.00</u>
		Transmission ☐	Cost \$ _____
Seat Belt Ready Seat	3-passenger position seat with securement belts.	Cost \$ <u>1,225.00</u>	
Seating System	Identical, non-lift bus with lap-shoulder seat belt system installed in all positions.	2 by 2 Cost \$ <u>12,718.00</u> Capacity <u>44</u> 3 by 2 Cost \$ <u>12,718.00</u> Capacity <u>44</u> 3 by 3 Cost \$ <u>16,184.00</u> Capacity <u>84</u>	

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C60 ☐ C77 ☐ D60 ☒ D84

Use this document to bid both non-lift and lift buses.

PART II (cont.)

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Storage Compartments	Largest available for unit bid.	Left side <u>36</u> cubic feet. Cost \$ <u>1,900.00</u> Right-side <u>36</u> cubic feet. Cost \$ <u>1,900.00</u> Push-thru <u>N/A</u> cubic feet. Cost \$ <u>N/A</u>	
Strobe Light	Exterior roof mounted white strobe light.	Mfr. <u>ECCO</u> Model No. <u>7460CC</u> Cost \$ <u>295.00</u>	
Student Protection System—Installed	Electronic system to insure driver post-trip inspection of passenger compartment.	Mfr. <u>THOMAS</u> Model No. <u>PASSENGER ADVISORY</u> Cost \$ <u>623.00</u>	
Suspension	Air ride (Air brake system only).	Front	Rear
		Cost \$ <u>N/A</u>	Cost \$ <u>4,025.00</u>
Toolbox	Interior, manufacturer standard.	Cost \$ <u>85.00</u> Deduct \$ <u>N/A</u>	
Traction Device	Automatic chains.	Mfr. <u>ON-SPOT</u> Cost \$ <u>6,192.00</u>	
Traction Device	Sanders.	Capacity <u>158LBS</u> Cost \$ <u>6,661.00</u>	
Transmission	Automatic—Allison, PTS 3000 or equal.	Mfr. <u>ALLISON</u> Model No. <u>3000PTS</u> Cost \$ <u>7,541.00</u>	
Vehicle Securement System	Must meet state specification.	Mfr. <u>SAFETY BRAKE</u>	Cost \$ <u>1,716.00</u>

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

☐ C60 ☐ C77 ☐ D60 ☒ D84

Use this document to bid both non-lift and lift buses.

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Video Camera Systems—Installed	Digital audio/video system for monitoring the passenger compartment with more than two cameras.	Mfr. <u>REI</u> Model No. <u>HD</u> Cost \$ <u>6,400.00</u> How many cameras <u>3</u>	
Video Camera Systems—Stop Sign Camera—Installed	Must meet state specification.	Stand Alone System Mfr. <u>REI</u> Model No. <u>HD</u> Cost \$ <u>7,104.00</u> How many cameras <u>4</u>	Added to Interior System Mfr. <u>REI</u> Model No. <u>HD</u> Cost \$ <u>633.00</u> How many cameras <u>1</u>
Warning Light Monitor	16 light monitoring system.	Incandescent Cost \$ <u>N/A</u>	LED Lights Cost \$ <u>780.00</u>
Additional Wheelchair/Occupant Tie-down System—Installed	Must meet state specification.	Mfr. <u>N/A</u> Model No. <u>N/A</u> Cost per station \$ <u>N/A</u>	
Windows	Laminated passenger-compartment side or rear glass.	Side Cost \$ <u>1,500.00</u> Rear Cost \$ <u>INCLUDED W/ SIDE COST</u> Both Cost \$ <u>1,500.00</u>	
Windows	Tinted.	Cost \$ <u>750.00</u>	
Windows	Thermal pane, left of driver and service door.	Cost \$ <u>895.00</u>	