

State Price Quote Specification
TYPE D—84 PASSENGER, REAR ENGINE
Use this document to bid both non-lift and lift buses for 61 – 84 capacity

PART I
Vendor: SCHETKY NW SALES
—
THOMAS BUILT BUS

ITEM	SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
Seating Capacity	84 passenger maximum design capacity seated for 78 passenger.	Capacity w/o lift <u>78</u> Capacity w/lift <u>N/A</u>
Alternator	240 amp minimum. Lift-equipped or air-conditioned. Manufacturer recommended capacity.	Mfr. <u>LEECE NEVILLE</u> Amps output w/o lift or A.C. <u>240</u> Amps output w/lift or A.C. <u>N/A</u>
Auxiliary Fans	2 fans, 6" maximum, mounted to right and left windshield and service door.	Mfr. <u>BERGSTROM</u>
Axle—Front	13,200 lb. minimum total suspension GVWR.	Mfr. <u>DETROIT</u> Capacity <u>13,200</u>
Axle—Rear	23,000 lb. minimum total suspension GVWR.	Mfr. <u>DANA 23,000LB CAPACITY</u> Capacity _____
Axle Oil Seals	Front and rear oil bath, or maintenance free sealed greased bearings.	Mfr. <u>CR</u>
Axle Ratio	Must comply with power and gradeability formula. Refer to Washington State School Bus Specifications Manual.	Ratio <u>5.57</u>
Back-up Lights	All required backup lights to be LED (Light Emitting Diode). Refer to Washington State School Bus Specification's Manual.	Round: ☐ Diameter _____ Other: ☒ Square inches <u>22</u>
Battery(ies)	1400 CCA 12 volt to be mounted in body battery compartment.	Number of batteries <u>3</u> CCA <u>2850</u>
Battery Compartment	Battery storage tray must be large enough to accommodate batteries as specified in chassis section.	☐ Swing out ☒ Roll out
Brakes	Air: Drum or Disc. If Drum, minimum 16.5" x 6" front, minimum 16.5" x 8" rear. Refer to Washington State School Bus Specifications Manual.	Disc Front ☐ Rear ☐ Drum Front ☒ Rear ☒ Size <u>16.5x6</u> Rear <u>16.5x8 5/8</u>
Door, Service	Power operated.	☐ Folding ☐ Other ☐ Roll out ☒ Split, Outward opening
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Mfr. <u>NATIONAL COMODORE</u>

State Price Quote Specification

PART I (cont.)

Vendor: SCHETKY NW SALES

TYPE D—84 PASSENGER, REAR ENGINE

THOMAS BUILT BUS

Use this document to bid both non-lift and lift buses for 61 – 84 capacity

ITEM	SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
Engine	Diesel—280 H.P. minimum, located in the rear.	Engine mfr. <u>CUMMINS</u> Model or liters <u>B6.7L</u> Net torque 660 _____ @ 1600 _____ R.P.M Net H.P. 280 _____ @ 2400 _____ R.P.M
Engine Heater	Engine manufacturers recommended in-block heater.	Watts <u>750</u> _____ Volts <u>115</u> _____ Mfr. <u>PHILLIPS</u> _____
Engine Temperature	To be controlled electronically, by fan clutch/drive, or shutters.	Mfr. <u>EATON</u> _____ ☐ Electronic ☒ Fan clutch ☐ Shutters
Fuel Tank	100 gallon minimum.	Capacity <u>100 GALLON</u> _____
Heaters	Minimum of 3 heaters; 1 front, 1 center, 1 rear. Shutoff valves at engine for all heaters. Two-speed motors. Must include recirculating pump.	Front B.T.U. <u>90,000</u> _____ Center B.T.U. <u>84,000</u> _____ Rear B.T.U. <u>84,000</u> _____ Total B.T.U. <u>258,000</u> _____
Lights	LED (Light Emitting Diode). Includes Clearance Lights, Stop Lights—7", Taillights, Turn Signals, Eight-Light System, and Dome-Light System.	Check if as specified ☒ If not, explain. _____
P.A. System	AM/FM/PA radio with 4 interior and 1 exterior speakers.	Mfr. <u>DELPHI</u> _____ Model No. <u>DEA700</u> _____
Seat Spacing	78 passenger based upon manufacturer's maximum seat spacing.	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: <u>396.50</u> inches Mfg.'s C/C seat measurement: <u>30</u> inches
Steering Wheel	Tilt and telescoping column.	Check if as specified ☒
Step Tread	Studded or pebbled top tread covering.	Mfr. <u>KOROSEAL</u> _____
Tires	6 first quality, radial ply.	Mfr. <u>HANKOOK AH37</u> _____ Size <u>11R22.5</u> _____ Load range <u>H</u> _____

PART I (cont.)

State Price Quote Specification TYPE D—84 PASSENGER, REAR ENGINE

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

ITEM	SPECIFICATIONS	VENDOR SPECIFICALLY IDENTIFY ITEM BID
	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	Price of items bid will establish the district cost.
Toolbox	Exterior, manufacturer standard.	Size (cubic feet) <u>8.9</u>
Transmission	Automatic—Allison, PTS 3000 or equal.	Mfr. <u>ALLISON</u>
		Model no. <u>3000PTS</u>
		Net input torque <u>660</u>
		Net input H.P. <u>280</u>
Two-way Communications	45-watt, VHF, mil. spec.	Mfr. <u>MOTORLA</u>
		Model No. <u>CM300D</u>
Wheels	6 to be compatible with tire size.	Size <u>22.5"</u>
		Rim width <u>8.25"</u>
	SPECIAL NEEDS REQUIREMENTS—CHASSIS AND BODY	
Wheelchair Lift—Installed	Must meet state specification. Platform shall be a minimum of 32" x 52".	Mfr. <u>N/A</u>
		Model No. <u>N/A</u>
Wheelchair/ Occupant Tie-down System—Installed	Must meet state specification.	Mfr. <u>N/A</u>
		Model No. <u>N/A</u>

State Price Quote Specification
TYPE D—84 PASSENGER, REAR ENGINE
 Use this document to bid both non-lift and lift buses for 61 – 84 capacity

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

ITEM	SPECIFICATIONS	VENDOR SPECIFICALLY IDENTIFY ITEM BID
	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	Price of items bid will establish the district cost.
	ADDITIONAL REQUIREMENTS—CHASSIS AND BODY	
Line Setting Ticket	Legible copy of manufacturer's Line Setting Ticket will be delivered with each vendor's packet at the time of delivery of the bus.	Check if as specified ☒
Owner's/Operator's Handbook	One copy of the chassis manufacturer's owner's/operator's handbook or manual will be furnished with each bus at time of delivery.	Check if as specified ☒
Repair Manuals	A complete set of chassis, engine, transmission, and body repair manuals, including wiring diagram for all components, will be made available at time of delivery, with instructions available on accessing repair materials.	Check if as specified ☒
Service and Cleaning	Cleaning and service by vendor prior to delivery will include: • Chassis lubrication. • Check fluid levels: verify all are at recommended full levels. • Cooling system protected at -20°F. • Interior and exterior will be clean (including glass). • All systems (electric, air, hydraulic, mechanical, and manual) be inspected to ensure proper operation at time of delivery. • All components and accessories will be installed and operational at time of delivery.	Check if as specified ☒
Warranty	A complete copy of all warranty agreements will be furnished at time of delivery.	Check if as specified ☒



Washington Office of Superintendent of
PUBLIC INSTRUCTION
2026-2027

STUDENT TRANSPORTATION
Old Capitol Building
PO BOX 47200
Olympia, WA 98504-7200
(360) 725-6120 TTY (360) 664-3631

VEHICLE DATA SHEET AND OFFICIAL PRICE QUOTATION TYPE D—84 PASSENGER, REAR ENGINE

VENDOR'S COMPANY NAME SCHETKY NW SALES, INC.		REPRESENTATIVE'S NAME SCOTT MEYER	TELEPHONE NUMBER 509-579-6267
ADDRESS 8430 NE LOMBARD ST. PORTLAND, OR. 97220		Estimated delivery date to school district from time purchase order is received: <u>240-260</u> Firm where engine and chassis can be serviced or repaired, and parts obtained: <u>SCHETKY</u> Firm where body can be serviced or repaired, and parts obtained: <u>SCHETKY</u>	

BODY

MAKE THOMAS	Warranty: Years <u>3</u> Miles <u>50,000</u>	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: w/o lift <u>396.5</u> w/lift <u>N/A</u>	Equipped seating capacity: w/o lift <u>78</u> w/lift <u>N/A</u>
MODEL 370DS	YEAR 2027	Seat color: <u>GREY</u> Floor color: <u>GREY</u>	Overall vehicle length (inches): w/o lift <u>469.9</u> w/lift <u>N/A</u>

CHASSIS

MAKE THOMAS	Warranty: Years <u>3</u> Miles <u>50,000</u>	MANUFACTURER CUMMINS	Torque: <u>660</u> @ <u>1600</u> RPM H.P.: <u>280</u> @ <u>2400</u> RPM
MODEL CHSY	YEAR 2027	Wheelbase: <u>267</u>	MODEL B6.7L
		YEAR 2027	C.I.D.: <u>6.7L</u> Fuel type: <u>DIESEL</u>

TRANSMISSION

MANUFACTURER ALLISON	Warranty: Years <u>5</u> Miles <u>100,000</u>	Battery type/grp: <u>31</u> <u>N/A</u>
MODEL 3000PTS	Speeds forward: <u>6</u>	Number batteries: <u>3</u> <u>N/A</u>
Warranty: Years <u>5</u> Miles <u>UNLIMITED</u>		Total CCA: <u>2850</u> <u>N/A</u>
Number of cylinders: <u>6</u> Inline <u>X</u> V-type <u> </u>		

QUOTED PRICE

Quoted price is based upon payment within 30 days after delivery to the school district (without sales tax).

Bid—w/o lift \$ 215,348.00

Bid—w/lift \$ NO BID

VENDOR REPRESENTATIVE'S SIGNATURE

Scott Meyer

DATE

7/31/2026

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C60 ☐ C77 ☐ D60 ☒ D84

Use this document to bid both non-lift and lift buses.

PART II

Vendor: SCHETKY NW

SALES

THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Activity Securement Seating	2-passenger position seats with lap-shoulder belts in all passenger positions.	Passenger Capacity <u>52</u> Cost \$ <u>650.00 PER SEAT, REPLACE STD SEAT</u>	
Air Conditioning	To cool passenger compartment as required in the Washington State School Bus Specifications manual.	Mfr. <u>CARRIER 106K BTU</u> Cost \$ <u>17,655.00</u>	
Alternate Fuel ☐ Electric	Must comply with power and gradeability formula. Refer to Washington State School Bus Specifications manual. Must comply with all the requirements of FMVSS No. 305.	Mfr. <u>N/A</u> ☐ Cost \$ <u>N/A</u> ☐ Electric Cost \$ <u>SEPARATE BID</u>	
Alternator	Available options.	Cost \$ <u>1,650.00</u> Capacity <u>270A</u> Cost \$ <u>2,225.00</u> Capacity <u>320A</u> Cost \$ <u>N/A</u> Capacity <u>N/A</u>	
Anti-spray Device	Rubber fender extenders.	Type C: Cost \$ <u>195.00</u> Type D: Cost \$ <u>375.00</u>	
Back-up Alarm	Must meet state specification.	Mfr. <u>ECCO 850N-TB2</u> Cost \$ <u>175.00</u>	
Brakes	4-wheel hydraulic disk brake.	Cost \$ <u>N/A</u>	Deduct \$ <u>N/A</u>
Brakes	Air, Drum or Disc. Refer to Washington State School Bus Specifications manual.	Disc Cost \$ <u>4,350.00</u> Drum Cost \$ <u>INCLUDED</u>	Disc Deduct \$ <u>N/A</u> Drum Deduct \$ <u>N/A</u>
Color	Exterior white roof.	Cost \$ <u>790.00</u>	
Door Locks	Vandal lock system on all exterior doors.	Cost \$ <u>350.00</u>	
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Non-Air	Air
		Mfr. <u>N/A</u>	Mfr. <u>NATIONAL</u>
		Cost \$ <u>N/A</u>	Cost \$ <u>INCLUDED</u>
Fire Suppression System	Jomarr VT-6-E-NAF, or equal engine compartment fire suppression system of appropriate size to be installed according to manufacturer recommendation.	Mfr. <u>FOGMAKER</u> Cost \$ <u>15,639.00</u>	
Floor Color	Nonstandard color.	Cost \$ <u>950.00</u>	

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C60 ☐ C77 ☐ D60 ☒ D84

Use this document to bid both non-lift and lift buses.

PART II (cont.)

Vendor: SCHETKY NW

SALES

THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Fuel Tank	Larger fuel capacity (Diesel only).	Size: <u>INCLUDED</u>	Cost \$ <u>N/A</u>
Fuel Tank	Larger fuel capacity (Propane only).	Size: <u>N/A</u>	Cost \$ <u>N/A</u>
Headlights	Halogen.	Cost \$ <u>INCLUDED</u>	
Headlights	L.E.D.	Cost \$ <u>1408.00</u>	
Heater (Auxiliary water)	Auxiliary fuel-fired heating systems. Refer to Washington State School Bus Specifications Manual, page 27.	Brand: <u>WEBASTO</u>	Model: <u>PRO90</u> Cost \$ <u>5,550.00</u>
Noise Reduction	Exceeding minimum specifications.	Driver compartment	Cost \$ <u>250.00</u>
		Engine compartment	Cost \$ <u>INCLUDED</u>
		Full acoustical headliner	Cost \$ <u>INCLUDED</u>
Retarder	Manufacturer's standard.	Driveline ☐	Cost \$ _____
		Exhaust ☒	Cost \$ <u>175.00</u>
		Transmission ☐	Cost \$ _____
Seat Belt Ready Seat	3-passenger position seat with securement belts.	Cost \$ <u>1,225.00</u>	
Seating System	Identical, non-lift bus with lap-shoulder seat belt system installed in all positions.	2 by 2 Cost \$ <u>12,718.00</u> Capacity <u>44</u> 3 by 2 Cost \$ <u>12,718.00</u> Capacity <u>44</u> 3 by 3 Cost \$ <u>16,184.00</u> Capacity <u>84</u>	

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C60 ☐ C77 ☐ D60 ☒ D84

Use this document to bid both non-lift and lift buses.

PART II (cont.)

Vendor: SCHEKTY NW

SALES

THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Storage Compartments	Largest available for unit bid.	Left side <u>21.4</u> cubic feet. Cost \$ <u>1,375.00</u> Right-side <u>21.4</u> cubic feet. Cost \$ <u>1,375.00</u> Push-thru <u>129</u> cubic feet. Cost \$ <u>5,600.00</u>	
Strobe Light	Exterior roof mounted white strobe light.	Mfr. <u>ECCO</u> Model No. <u>7460CC</u> Cost \$ <u>295.00</u>	
Student Protection System—Installed	Electronic system to insure driver post-trip inspection of passenger compartment.	Mfr. <u>THOMAS</u> Model No. <u>PASSENGER ADVISORY</u> Cost \$ <u>623.00</u>	
Suspension	Air ride (Air brake system only).	Front Cost \$ <u>3004.00</u>	Rear Cost \$ <u>INCLUDED</u>
Toolbox	Interior, manufacturer standard.	Cost \$ <u>85.00</u> Deduct \$ <u>N/A</u>	
Traction Device	Automatic chains.	Mfr. <u>ON-SPOT</u> Cost \$ <u>6,192.00</u>	
Traction Device	Sanders.	Capacity <u>158LBS</u> Cost \$ <u>6,661.00</u>	
Transmission	Automatic—Allison, PTS 3000 or equal.	Mfr. <u>ALLISON</u> Model No. <u>3000PTS</u> Cost \$ <u>INCLUDED</u>	
Vehicle Securement System	Must meet state specification.	Mfr. <u>SAFETY BRAKE</u>	Cost \$ <u>1,716.00</u>

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C60 ☐ C77 ☐ D60 ☒ D84

Use this document to bid both non-lift and lift buses.

PART II (cont.)

Vendor: SCHETKY NW

SALES

THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Video Camera Systems—Installed	Digital audio/video system for monitoring the passenger compartment with more than two cameras.	Mfr. <u>REI</u> Model No. <u>HD</u> Cost \$ <u>6,400.00</u> How many cameras <u>3</u>	
Video Camera Systems—Stop Sign Camera—Installed	Must meet state specification.	Stand Alone System Mfr. <u>REI</u> Model No. <u>HD</u> Cost \$ <u>7,104.00</u> How many cameras <u>4</u>	Added to Interior System Mfr. <u>REI</u> Model No. <u>HD</u> Cost \$ <u>633.00</u> How many cameras <u>1</u>
Warning Light Monitor	16 light monitoring system.	Incandescent Cost \$ <u>N/A</u>	LED Lights Cost \$ <u>780.00</u>
Additional Wheelchair/Occupant Tie-down System—Installed	Must meet state specification.	Mfr. <u>N/A</u> Model No. <u>N/A</u> Cost per station \$ <u>N/A</u>	
Windows	Laminated passenger-compartment side or rear glass.	Side Cost \$ <u>1,500.00</u> Rear Cost \$ <u>INCLUDED W/ SIDE COST</u> Both Cost \$ <u>1,500.00</u>	
Windows	Tinted.	Cost \$ <u>750.00</u>	
Windows	Thermal pane, left of driver and service door.	Cost \$ <u>895.00</u>	